


ARKON

Data transmission builds bridges

Expands the possibilities



No software adaption

As soon as the cables are connected and ARKON is powered, ARKON automatically transmits the MIRUS data



Fast data transmission

ARKON starts data recording immediately after uncomplicated connection to the MIRUS Controller and the patient monitor




Live values

The MIRUS data are permanently updated on the patient monitor



Space saving

With its small, sleek housing, the ARKON can be easily integrated and mounted



Device independent

If MIRUS Controller or patient monitor changes, ARKON automatically readjusts



ARKON Data Bridge is a medical device for transmitting data signals from the MIRUS Controller to a patient monitor. During operation, measured values and alarms are transmitted unencrypted and unchanged.

General specifications

Physical dimensions

<i>Width x Height x Depth</i>	950 mm x 310 mm x 600 mm	<i>Weight</i>	450 g
-------------------------------	--------------------------	---------------	-------

Environmental conditions (during operation)

<i>Temperature range</i>	15 to 35 °C	<i>Atm. Pressure range</i>	700 to 1.100 hPa
<i>Humidity range</i>	10 to 95 % relative, none condensing		

Environmental conditions (storage and transport)

<i>Temperature range</i>	-20 to 60 °C	<i>Atm. Pressure range</i>	500 to 1.200 hPa
<i>Humidity range</i>	10 to 95 % relative, none condensing		

Classification

<i>CE class according 93/42/EEC</i>	I	<i>IP code</i>	IP20
<i>Protection class according to EN 60601-1</i>	II	<i>Protection type according to EN 60601-1</i>	B

Standards applied	EN 60601-1	EN 60601-1-1
--------------------------	------------	--------------

UMDNS Code	17-762
-------------------	--------

Electrical Power supply unit

<i>Supply voltage</i>	100 to 240 V _{AC} ± 10%	<i>Frequency</i>	50 to 60 Hz ± 5%
<i>Power consumption</i>	< 15 VA		

Electrical supply Device

<i>Nominal voltage</i>	5 V Direct current	<i>Amperage</i>	Max 2.5 A
------------------------	--------------------	-----------------	-----------

Versions

ARKON-PH Compatible to Philips patient monitors via IntelliBridge EC 10:
IntelliVue MP series (SW version H.15 or higher), IntelliVue MX series (all SW versions)
Compatible to Philips control panels via IntelliBridge EC40/80:
PIIC iX (SW version B.0), PIC iX (SW version C.0 or higher)
Compatible drivers: Open Interface IB-ED101-A.6 or higher



Technologie Institut Medizin GmbH (TIM)
August-Thyssen-Str. 30, 56070 Koblenz
Germany

Tel.: +49 261 899 689 00

Fax.: +49 261 899 689 09

www.tim-gmbh.de

info@tim-gmbh.de



Specifications are subjects to change without prior notice.

ARKON flyer ©2021 TIM GmbH.

All rights reserved. Rev. D-00 of 09/21.

TIM is a trademark of TIM GmbH.



Visit us

www.tim-gmbh.de

Sales Partner: